



Rotation Angle Plug nipple with internal thread conical

| | |
|----------------------|------------------------------|
| medium: | compressed air vacuum |
| body material: | plastic, nickel-plated brass |
| maximum pressure: | 10 bar (vacuum) |
| working temperature: | -20 To + 60 ° C |
| seal thread: | O-ring or PTFE coating |

| Name | Screw | Waż | L1 (mm) | L2 (mm) | SW |
|------------|--------|-----|---------|---------|----|
| 153.018-4 | Rc 1/8 | 4 | 18 | 23,0 | 14 |
| 153.018-6 | Rc 1/8 | 6 | 19 | 39 | 14 |
| 153.018-8 | Rc 1/8 | 8 | 23 | 27 | 14 |
| 153.014-6 | Rc 1/4 | 6 | 19 | 27 | 17 |
| 153.014-8 | Rc 1/4 | 8 | 23 | 30,0 | 17 |
| 153.014-10 | Rc 1/4 | 10 | 30,0 | 34 | 17 |
| 153.014-12 | Rc 1/4 | 12 | 30,0 | 37,0 | 21 |
| 153.038-8 | Rc 3/8 | 8 | 23 | 32,0 | 21 |
| 153.038-10 | Rc 3/8 | 10 | 30,0 | 36 | 21 |
| 153.038-12 | Rc 3/8 | 12 | 30,0 | 38,0 | 21 |
| 153.012-8 | Rc 1/2 | 8 | 23 | 34 | 24 |
| 153.012-10 | Rc 1/2 | 10 | 30,0 | 38,0 | 24 |
| 153.012-12 | Rc 1/2 | 12 | 30,0 | 41,0 | 24 |