



## Tee male T rotatable with an external thread (o-ring) to the side

medium:

body material:

maximum pressure:

Operating temperature:

seal thread:

Application to conductors:

compressed air, vacuum

plastic, nickel-plated brass

15 bar (vacuum)

0 to + 80 ° C

O-ring NBR

PU, PA, PE

Name	Screw	L1 (mm)	L2 (mm)	SW	Waż
129.005-4	M5	17,5	33,5	10	4
129.005-6	M5	19	36,7	12	6
129.018-4	G1/8	17,7	35,5	14	4
129.018-6	G1/8	19,3	39,2	14	6
129.018-8	G1/8	22,8	44,3	14	8
129.018-10	G1/8	27,6	54,3	17	10
129.018-12	G1/8	29,6	60,5	27	12
129.014-4	G1/4	17,7	39	17	4
129.014-6	G1/4	19,3	42,2	17	6
129.014-8	G1/4	22,8	46,8	17	8
129.014-10	G1/4	27,6	56,3	17	10
129.014-12	G1/4	29,6	61,5	21	12
129.038-6	G3/8	19,3	43,7	20	6
129.038-8	G3/8	22,8	48,4	20	8
129.038-10	G3/8	27,6	57,3	20	10
129.038-12	G3/8	29,6	62,5	21	12
129.038-16	G3/8	33,0	72,5	24	16
129.012-6	G1/2	19,3	46,2	24	6
129.012-8	G1/2	22,8	50,8	24	8
129.012-10	G1/2	27,6	60,8	24	10
129.012-12	G1/2	29,6	65,5	24	12
129.012-16	G1/2	33,0	76	24	16