



Tee male T rotatable with an external thread (Teflon) from the side

| | |
|----------------------------|------------------------------|
| medium: | compressed air, vacuum |
| body material: | plastic, nickel-plated brass |
| maximum pressure: | 15 bar (vacuum) |
| Operating temperature: | 0 to + 80 ° C |
| seal thread: | O-ring NBR |
| Application to conductors: | PU, PA, PE |

| Name | Screw | Wąż | L1 (mm) | L2 (mm) | SW |
|------------|-------|-----|---------|---------|----|
| 130.018-4 | R1/8 | 4 | 18,5 | 43,5 | 10 |
| 130.018-6 | R1/8 | 6 | 19,5 | 45,3 | 12 |
| 130.018-8 | R1/8 | 8 | 21,5 | 52,2 | 14 |
| 130.018-10 | R1/8 | 10 | 28,1 | 63,3 | 17 |
| 130.014-4 | R1/4 | 4 | 18,5 | 46,5 | 14 |
| 130.014-6 | R1/4 | 6 | 19,5 | 47,8 | 14 |
| 130.014-8 | R1/4 | 8 | 21,5 | 54,2 | 14 |
| 130.014-10 | R1/4 | 10 | 27,5 | 65,3 | 17 |
| 130.014-12 | R1/4 | 12 | 29,5 | 68,1 | 21 |
| 130.038-6 | R3/8 | 6 | 19,5 | 49,3 | 17 |
| 130.038-8 | R3/8 | 8 | 21,5 | 55,7 | 17 |
| 130.038-10 | R3/8 | 10 | 27,5 | 66,3 | 17 |
| 130.038-12 | R3/8 | 12 | 29,5 | 69,1 | 21 |
| 130.038-16 | R3/8 | 16 | 32,5 | 76 | 24 |
| 130.012-6 | R1/2 | 6 | 19,5 | 52,8 | 21 |
| 130.012-8 | R1/2 | 8 | 21,5 | 59,2 | 21 |
| 130.012-10 | R1/2 | 10 | 27,5 | 69,8 | 21 |
| 130.012-12 | R1/2 | 12 | 29,5 | 72,1 | 21 |
| 130.012-16 | R1/2 | 16 | 32,5 | 79 | 24 |