



AB 45 - tip bent BSP

Application

Swage nipple for HD 100 to HD 400, KP and TE hoses

Connection 1
 Sealing form 1
 Short code
 Standard

BSP nut thread
 60° outer cone
 DKR
 ISO 8434-6
 BS 5200

Material
 Surface

Steel
 electro galvanised

Name	DN	Size	Screw
PN 04 AB 45	4	3	1/8"
PN 04 AB 06 45	4	3	1/4"
PN 06 AB 02 45	6	4	1/8"
PN 06 AB 45	6	4	1/4"
PN 06 AB 10 45	6	4	3/8"
PN 08 AB 06 45	8	5	1/4"
PN 08 AB 10 45	8	5	3/8"
PN 08 AB 13 45	8	5	1/2"
PN 10 AB 06 45	10	6	1/4"
PN 10 AB 45	10	6	3/8"
PN 10 AB 13 45	10	6	1/2"
PN 13 AB 10 45	13	8	3/8"
PN 13 AB 45	13	8	1/2"
PN 13 AB 16 45	13	8	5/8"
PN 13 AB 20 45	13	8	3/4"
PN 16 AB 13 45	16	10	1/2"
PN 16 AB 45	16	10	5/8"
PN 16 AB 20 45	16	10	3/4"
PN 16 AB 25 45	16	10	1"
PN 20 AB 13 45	20	12	1/2"
PN 20 AB 16 45	20	12	5/8"
PN 20 AB 45	20	12	3/4"
PN 20 AB 25 45	20	12	1"
PN 25 AB 45	25	16	1"
PN 25 AB 32 45	25	16	1 1/4"
PN 32 AB 45	32	20	1 1/4"
PN 32 AB 40 45	32	20	1 1/2"
PN 40 AB 45	40	24	1 1/2"

Name	DN	Size	Screw
PN 40 AB 50 45	40	24	2"
PN 50 AB 45	50	32	2"