



Tee Y rotary plug with an external thread (Teflon)

| | |
|----------------------|------------------------------|
| Medium: | compressed air vacuum |
| Housing material: | plastic, nickel-plated brass |
| Maximum pressure: | 10 bar (vacuum) |
| Working temperature: | -20 To + 60 ° C |
| Seal thread: | O-ring or PTFE coating |

| Name | Screw | Waż | L1 (mm) | SW |
|------------|-------|-----|---------|----|
| 134.018-4 | R1/8 | 4 | 42,0 | 10 |
| 134.018-6 | R1/8 | 6 | 43,8 | 12 |
| 134.018-8 | R1/8 | 8 | 47,1 | 14 |
| 134.014-4 | R1/4 | 4 | 45,0 | 14 |
| 134.014-6 | R1/4 | 6 | 46,3 | 14 |
| 134.014-8 | R1/4 | 8 | 49,1 | 14 |
| 134.014-10 | R1/4 | 10 | 58,4 | 17 |
| 134.014-12 | R1/4 | 12 | 60,7 | 21 |
| 134.038-6 | R3/8 | 6 | 47,8 | 17 |
| 134.038-8 | R3/8 | 8 | 50,6 | 17 |
| 134.038-10 | R3/8 | 10 | 59,4 | 17 |
| 134.038-12 | R3/8 | 12 | 61,7 | 21 |
| 134.012-6 | R1/2 | 6 | 51,3 | 21 |
| 134.012-8 | R1/2 | 8 | 54,1 | 21 |
| 134.012-10 | R1/2 | 10 | 62,9 | 21 |
| 134.012-12 | R1/2 | 12 | 65,7 | 21 |