

AB 90 - tip bent BSP



Application

Swage nipple for HD 100 to HD 400, KP and TE hoses

Connection 1
 Sealing form 1
 Short code
 Standard

BSP nut thread
 60° outer cone
 DKR
 ISO 8434-6
 BS 5200

Material
 Surface

Steel
 electro galvanised

Name	DN	Size	Screw
PN 04 AB 90	4	3	1/8"
PN 04 AB 06 90	4	3	1/4"
PN 06 AB 02 90	6	4	1/8"
PN 06 AB 90	6	4	1/4"
PN 06 AB 10 90	6	4	3/8"
PN 08 AB 06 90	8	5	1/4"
PN 08 AB 10 90	8	5	3/8"
PN 08 AB 13 90	8	5	1/2"
PN 10 AB 06 90	10	6	1/4"
PN 10 AB 90	10	6	3/8"
PN 10 AB 13 90	10	6	1/2"
PN 13 AB 10 90	13	8	3/8"
PN 13 AB 90	13	8	1/2"
PN 13 AB 16 90	13	8	5/8"
PN 13 AB 20 90	13	8	3/4"
PN 16 AB 13 90	16	10	1/2"
PN 16 AB 90	16	10	5/8"
PN 16 AB 20 90	16	10	3/4"
PN 16 AB 25 90	16	10	1"
PN 20 AB 13 90	20	12	1/2"
PN 20 AB 16 90	20	12	5/8"
PN 20 AB 90	20	12	3/4"
PN 20 AB 25 90	20	12	1"
PN 25 AB 90	25	16	1"
PN 25 AB 32 90	25	16	1 1/4"
PN 32 AB 90	32	20	1 1/4"
PN 32 AB 40 90	32	20	1 1/2"
PN 40 AB 90	40	24	1 1/2"

Name	DN	Size	Screw
PN 40 AB 50 90	40	24	2"
PN 50 AB 90	50	32	2"