

AB 90 - tip bent BSP



Application

Swage nipple for HD 100 to HD 400, KP and TE hoses

Connection 1
 Sealing form 1
 Short code
 Standard

BSP nut thread
 60° outer cone
 DKR
 ISO 8434-6
 BS 5200

Material
 Surface

Steel
 electro galvanised

| Name | DN | Size | Screw |
|----------------|----|------|--------|
| PN 04 AB 90 | 4 | 3 | 1/8" |
| PN 04 AB 06 90 | 4 | 3 | 1/4" |
| PN 06 AB 02 90 | 6 | 4 | 1/8" |
| PN 06 AB 90 | 6 | 4 | 1/4" |
| PN 06 AB 10 90 | 6 | 4 | 3/8" |
| PN 08 AB 06 90 | 8 | 5 | 1/4" |
| PN 08 AB 10 90 | 8 | 5 | 3/8" |
| PN 08 AB 13 90 | 8 | 5 | 1/2" |
| PN 10 AB 06 90 | 10 | 6 | 1/4" |
| PN 10 AB 90 | 10 | 6 | 3/8" |
| PN 10 AB 13 90 | 10 | 6 | 1/2" |
| PN 13 AB 10 90 | 13 | 8 | 3/8" |
| PN 13 AB 90 | 13 | 8 | 1/2" |
| PN 13 AB 16 90 | 13 | 8 | 5/8" |
| PN 13 AB 20 90 | 13 | 8 | 3/4" |
| PN 16 AB 13 90 | 16 | 10 | 1/2" |
| PN 16 AB 90 | 16 | 10 | 5/8" |
| PN 16 AB 20 90 | 16 | 10 | 3/4" |
| PN 16 AB 25 90 | 16 | 10 | 1" |
| PN 20 AB 13 90 | 20 | 12 | 1/2" |
| PN 20 AB 16 90 | 20 | 12 | 5/8" |
| PN 20 AB 90 | 20 | 12 | 3/4" |
| PN 20 AB 25 90 | 20 | 12 | 1" |
| PN 25 AB 90 | 25 | 16 | 1" |
| PN 25 AB 32 90 | 25 | 16 | 1 1/4" |
| PN 32 AB 90 | 32 | 20 | 1 1/4" |
| PN 32 AB 40 90 | 32 | 20 | 1 1/2" |
| PN 40 AB 90 | 40 | 24 | 1 1/2" |

| Name | DN | Size | Screw |
|----------------|-----------|-------------|--------------|
| PN 40 AB 50 90 | 40 | 24 | 2" |
| PN 50 AB 90 | 50 | 32 | 2" |