



HR - simple tip BSP flat sealing, male thread

Application

Swage nipple for HD 100 to HD 400, KP and TE hoses

Connection 1
 Sealing form 1

BSP external thread, cylindrical flat sealing

Short code

AGR-Flat

Material

Steel

Surface

electro galvanised

Name	DN	Size	Screw
PN 04 HR	4	3	1/8"
PN 04 HR 06	4	3	1/4"
PN 06 HR 02	6	4	1/8"
PN 06 HR	6	4	1/4"
PN 06 HR 10	6	4	3/8"
PN 08 HR 06	8	5	1/4"
PN 08 HR 10	8	5	3/8"
PN 08 HR 13	8	5	1/2"
PN 10 HR 06	10	6	1/4"
PN 10 HR	10	6	3/8"
PN 10 HR 13	10	6	1/2"
PN 13 HR 10	13	8	3/8"
PN 13 HR	13	8	1/2"
PN 13 HR 16	13	8	5/8"
PN 13 HR 20	13	8	3/4"
PN 16 HR 13	16	10	1/2"
PN 16 HR	16	10	5/8"
PN 16 HR 20	16	10	3/4"
PN 16 HR 25	16	10	1"
PN 20 HR 13	20	12	1/2"
PN 20 HR 16	20	12	5/8"
PN 20 HR	20	12	3/4"
PN 20 HR 25	20	12	1"
PN 25 HR	25	16	1"
PN 25 HR 32	25	16	1 1/4"
PN 32 HR	32	20	1 1/4"
PN 32 HR 40	32	20	1 1/2"
PN 40 HR	40	24	1 1/2"

Name	DN	Size	Screw
PN 40 HR 50	40	24	2"
PN 50 HR	50	32	2"