



6310 - mini ball valve, thread a conical outer / inner, nickel-plated brass

| | |
|----------------------|----------------------------|
| Housing material: | brass n iklowany |
| Material Ball: | chrome plated brass |
| Handle material: | plastic (PA66) |
| Ball seal: | Teflon (PTFE) |
| Sealing: | NBR (Viton on request) |
| Pressure: | max.20bar |
| Working temperature: | from -18 °C to 80 °C |
| Medium: | Compressed air, water, oil |

| Name | A | B | DN | ES | F | M | L | G | H |
|-----------------------------|---|-----|-----|-------|------|------|------|----|------|
| 6310 1/8-1/8 1/8 BLUE PL | | 1/8 | - | 14-15 | 7.4 | 7 | 36 | 19 | 20 |
| 6310 1/8-1/8 1/8 | | 1/8 | 5.5 | 14-15 | 7.4 | 7.4 | 36 | 19 | 12 |
| 6310 1/4-1/8 1/4 | | 1/8 | 5.5 | 14-15 | 11 | 11 | 40,5 | 19 | 21 |
| 6310 1/4-1/4 1/4 | | 1/4 | 5.5 | 14-15 | 11 | 11 | 43 | 19 | 21 |
| 6310 3/8-3/8 3/8 | | 3/8 | 8 | 18-19 | 11.4 | 11.4 | 46 | 19 | 22 |
| 6310 1/2-1/2 1/2 | | 1/2 | 10 | 22-23 | 15 | 15 | 57 | 26 | 30,5 |
| 6310 3/4-3/4 3/4 | | 3/4 | 14 | 28-30 | 16.3 | 16.3 | 63 | 50 | 33 |