



6350 - Mini ball valve, conical outer thread / connection for CU pipe, nickel-plated brass

Housing material: brass n iklowany
 Material Ball: chrome plated brass
 Handle material: plastic (PA66)
 Ball seal: Teflon (PTFE)
 Sealing: NBR (Viton on request)
 Pressure: max.20bar
 Working temperature: from -18 °C to 80 °C
 Medium:

Compressed air, water, oil

| Name | A | D | DN | ES | F | L | G | H |
|-------------|-----|------|-----|-------|------|------|----|------|
| 6350 1/8-6 | 1/8 | 6 | 5.5 | 14-15 | 7.4 | 40,5 | 19 | 21 |
| 6350 1/8-8 | 1/8 | 8 | 5.5 | 14-15 | 7.4 | 40,5 | 19 | 21 |
| 6350 1/4-6 | 1/4 | 6 | 5.5 | 14-15 | 11 | 46 | 19 | 21 |
| 6350 1/4-8 | 1/4 | 8 | 5.5 | 14-15 | 11 | 45 | 19 | 21 |
| 6350 3/8-10 | 3/8 | 10,0 | 8 | 18-19 | 11.4 | 50,5 | 19 | 22 |
| 6350 3/8-12 | 3/8 | 12 | 8 | 18-19 | 11.4 | 51,5 | 19 | 22 |
| 6350 1/2-14 | 1/2 | 14,0 | 10 | 22-23 | 15 | 59,5 | 26 | 30,5 |
| 6350 1/2-15 | 1/2 | 15,0 | 10 | 22-23 | 15 | 59,5 | 26 | 30,5 |
| 6350 3/4-16 | 3/4 | 16 | 14 | 28-30 | 16.3 | 67 | 50 | 33 |
| 6350 3/4-18 | 3/4 | 18,0 | 14 | 28-30 | 16.3 | 67 | 50 | 33 |