



6420 - Mini ball valve, thread parallel external / external brass nickel-plated

Housing material:	brass n iklowany
Material Ball:	chrome plated brass
Handle material:	plastic (PA66)
Ball seal:	Teflon (PTFE)
Sealing:	NBR (Viton on request)
Pressure:	max.20bar
Working temperature:	from -18 °C to 80 °C
Medium:	

Compressed air, water, oil

Name	A	B	DN	ES	F	M	L	G	H
6420 1/8-1/8 1/8	1/8	1/8	5.5	14-15	7	7	32	19	21
6420 1/8-1/4 1/8	1/8	1/4	5.5	14-15	7	8	32	19	21
6420 1/4-1/4 1/4	1/4	1/4	5.5	14-15	8	8	33	19	21
6420 3/8-1/4 3/8	1/4	3/8	5.5	14-15	9	8	33	19	21
6420 3/8-3/8 3/8	3/8	3/8	8	18-19	9	9	37	19	22
6420 1/2-3/8 1/2	3/8	1/2	8	18-19	10	9	37	19	22
6420 1/2-1/2 1/2	1/2	1/2	10	22-23	10	10	42	26	30,5
6420 3/4-1/2 3/4	1/2	3/4	10	22-23	12	10	42	50	30,5
6420 3/4-3/4 3/4	3/4	3/4	14	28-30	12	12	49	50	33