



6420 - Mini ball valve, thread parallel external / external brass nickel-plated

| | |
|----------------------|------------------------|
| Housing material: | brass n iklowany |
| Material Ball: | chrome plated brass |
| Handle material: | plastic (PA66) |
| Ball seal: | Teflon (PTFE) |
| Sealing: | NBR (Viton on request) |
| Pressure: | max.20bar |
| Working temperature: | from -18 °C to 80 °C |
| Medium: | |

Compressed air, water, oil

| Name | A | B | DN | ES | F | M | L | G | H |
|------------------|-----|-----|-----|-------|----|----|----|----|------|
| 6420 1/8-1/8 1/8 | 1/8 | 1/8 | 5.5 | 14-15 | 7 | 7 | 32 | 19 | 21 |
| 6420 1/8-1/4 1/8 | 1/8 | 1/4 | 5.5 | 14-15 | 7 | 8 | 32 | 19 | 21 |
| 6420 1/4-1/4 1/4 | 1/4 | 1/4 | 5.5 | 14-15 | 8 | 8 | 33 | 19 | 21 |
| 6420 3/8-1/4 3/8 | 1/4 | 3/8 | 5.5 | 14-15 | 9 | 8 | 33 | 19 | 21 |
| 6420 3/8-3/8 3/8 | 3/8 | 3/8 | 8 | 18-19 | 9 | 9 | 37 | 19 | 22 |
| 6420 1/2-3/8 1/2 | 3/8 | 1/2 | 8 | 18-19 | 10 | 9 | 37 | 19 | 22 |
| 6420 1/2-1/2 1/2 | 1/2 | 1/2 | 10 | 22-23 | 10 | 10 | 42 | 26 | 30,5 |
| 6420 3/4-1/2 3/4 | 1/2 | 3/4 | 10 | 22-23 | 12 | 10 | 42 | 50 | 30,5 |
| 6420 3/4-3/4 3/4 | 3/4 | 3/4 | 14 | 28-30 | 12 | 12 | 49 | 50 | 33 |