



6440 - Mini ball valve, external parallel thread / connection for CU pipe, nickel-plated brass

Housing material: brass n iklowany
 Material Ball: chrome plated brass
 Handle material: plastic (PA66)
 Ball seal: Teflon (PTFE)
 Sealing: NBR (Viton on request)
 Pressure: max.20bar
 Working temperature: from -18 °C to 80 °C
 Medium:

Compressed air, water, oil

Name	A	D	DN	ES	F	L	G	H
6440 1/8-6	1/8	6	5.5	14-15	7	39	19	21
6440 1/8-8	1/8	8	5.5	14-15	7	40	19	21
6440 1/4-6	1/4	6	5.5	14-15	8	40	19	21
6440 1/4-8	1/4	8	5.5	14-15	8	41	19	21
6440 1/4-10	1/4	10,0	5.5	14-15	8	44	19	21
6440 3/8-8	3/8	8	5.5	14-15	9	43	19	21
6440 3/8-10	3/8	10,0	8	18-19	9	46	19	22
6440 3/8-12	3/8	12	8	18-19	9	47	19	22
6440 3/8-14	3/8	14,0	8	18-19	9	50,5	19	22
6440 3/8-15	3/8	15,0	8	18-19	9	50,5	19	22
6440 1/2-10	1/2	10,0	8	18-19	10	49	19	22
6440 1/2-12	1/2	12	8	18-19	10	50	19	22
6440 1/2-14	1/2	14,0	10	22-23	10	52,5	26	30,5
6440 1/2-15	1/2	15,0	10	22-23	10	52,5	26	30,5
6440 3/4-14	3/4	14,0	10	22-23	12	56,5	26	30,5
6440 3/4-15	3/4	15,0	10	22-23	12	56,5	26	30,5
6440 3/4-16	3/4	16	14	28-30	12	60,5	50	33
6440 3/4-18	3/4	18,0	14	28-30	12	60,5	50	33