



6450 - Mini ball valve, connection tubes CU / CU connection to pipes, nickel-plated brass

Housing material:	brass n iklowany
Material Ball:	chrome plated brass
Handle material:	plastic (PA66)
Ball seal:	Teflon (PTFE)
Sealing:	NBR (Viton on request)
Pressure:	max.20bar
Working temperature:	from -18 °C to 80 °C
Medium:	

Compressed air, water, oil

Name	D1 (mm)	D	DN	ES	L	G	H
6450 6-6	6	6	5.5	14-15	46	19	21
6450 6-8	6	8	5.5	14-15	48	19	21
6450 8-8	8	8	5.5	14-15	48	19	21
6450 10-8	10	8	5.5	14-15	51	19	21
6450 10-10	10	10,0	8	18-19	55	19	22
6450 10-12	10	12	8	18-19	56	19	22
6450 12-12	12	12	8	18-19	57	19	22
6450 14-10	14	10,0	8	18-19	59,5	19	22
6450 14-12	14	12	8	18-19	60,5	19	22
6450 14-14	14	14,0	10	18-19	63	26	30,5
6450 15-10	15	10,0	8	18-19	59,5	19	22
6450 15-12	15	12	8	18-19	60,5	19	22
6450 15-14	15	14,0	10	22-23	63	26	30,5
6450 15-15	15	15,0	10	22-23	63	26	30,5
6450 16-14	16	14,0	10	22-23	68	26	30,5
6450 16-15	16	15,0	10	22-23	68	26	30,5
6450 18-14	18	14,0	10	22-23	68	26	30,5
6450 18-15	18	15,0	10	22-23	68	26	30,5
6450 18-16	18	16	14	28-30	71	50	33
6450 18-18	18	18,0	14	28-30	71	50	33