

SF 90 - bent flanged tip - a variety of light



Application

Swage nipple for HD 100 to HD 400, KP and TE hoses

Connection 1
 Sealing form 1
 Short code
 Standard

SAE flange connection 3000 PSI
 flat seal with SF O-ring

SFL
 SAE J518
 ISO 6162-1

Material
 Surface

Steel
 electro galvanised

Name	DN	Size	Średnica kołnierza
PN 13 SF 90	13	8	30,2
PN 13 SF 20 90	13	8	38,1
PN 16 SF 13 90	16	1"	30,2
PN 16 SF 20 90	16	1"	38,1
PN 16 SF 25 90	16	1"	44,4
PN 20 SF 13 90	20	12	30,2
PN 20 SF 90	20	12	38,1
PN 20 SF 25 90	20	12	44,4
PN 25 SF 20 90	25	16	38,1
PN 25 SF 90	25	16	44,4
PN 25 SF 32 90	25	16	50,8
PN 32 SF 25 90	32	20	44,4
PN 32 SF 90	32	20	50,8
PN 32 SF 40 90	32	20	60,3
PN 40 SF 90	40	24	60,3
PN 40 SF 32 90	40	24	50,8
PN 40 SF 50 90	40	24	71,4
PN 50 SF 40 90	50	32	60,3
PN 50 SF 90	50	32	71,4
PN 50 SF 60 90	50	32	84