

SF6 90 - Swage nipple, SFS angle 90°



Application

Swage nipple for HD 100 to HD 400, KP and TE hoses

Connection 1

SAE flange connection 6000 PSI

Sealing form 1

flat seal with SF O-ring

Short code

SFS

Standard

SAE J518

ISO 6162-2

Material

Steel

Surface

electro galvanised

Name	DN	Size	Średnica kołnierza
PN 13 SF 6 90	13	8	31,7
PN 13 SF 6 20 90	13	8	41,3
PN 16 SF 6 13 90	16	10	31,7
PN 16 SF 6 20 90	16	10	41,3
PN 16 SF 6 25 90	16	10	47,6
PN 20 SF 6 13 90	20	12	31,7
PN 20 SF 6 90	20	12	41,3
PN 20 SF 6 25 90	20	12	47,6
PN 25 SF 6 20 90	25	16	41,3
PN 25 SF 6 90	25	16	47,6
PN 25 SF 6 32 90	25	16	54
PN 32 SF 6 25 90	32	20	47,6
PN 32 SF 6 90	32	20	54
PN 32 SF 6 40 90	32	20	63,5
PN 40 SF 6 32 90	40	24	54
PN 40 SF 6 90	40	24	63,5
PN 40 SF 6 50 90	40	24	79,4
PN 50 SF 6 40 90	50	32	63,5
PN 50 SF 6 90	50	32	79,4