



DMO NW 08 L - Connector

Connection 1
Sealing form 1
Connection 2
Sealing form 2
Design
Construction
Standard

Material
Surface

metric nut thread
 24° outer cone with O-ring
 metric nut thread
 24° outer cone with O-ring
 Fitting, double nuts
 straight
 DIN 2353
 ISO 8434-1
 Steel
 electro galvanised

Name	Ciśnienie	G1	G2	Budowa
DMO NW 04 L	100	M 12x1,5	M 12x1,5	L
DMO NW 06 L	400	M 14x1,5	M 14x1,5	L
DMO NW 08	400	M 16x1,5	M 16x1,5	L
DMO NW 10 L	400	M 18x1,5	M 18x1,5	L
DMO NW 13 L	400	M 22x1,5	M 22x1,5	L
DMO NW 16 L	315	M 26x1,5	M 26x1,5	L
DMO NW 20 L	315	M 30x2	M 30x2	L
DMO NW 25 L	250	M 36x2	M 36x2	L
DMO NW 32 L	250	M 45x2	M 45x2	L
DMO NW 40 L	250	M 52x2	M 52x2	L
DMO NW 03 S	630	M 14x1,5	M 14x1,5	S
DMO NW 04 S	630	M 16x1,5	M 16x1,5	S
DMO NW 06 S	630	M 18x1,5	M 18x1,5	S
DMO NW 08 S	630	M 20x1,5	M 20x1,5	S
DMO NW 10 S	630	M 22x1,5	M 22x1,5	S
DMO NW 13 S	400	M 24x1,5	M 24x1,5	S
DMO NW 16 S	400	M 30x2	M 30x2	S
DMO NW 20 S	400	M 36x2	M 36x2	S
DMO NW 25 S	400	M 45x2	M 45x2	S
DMO NW 32 S	315	M 52x2	M 52x2	S