

VEW NW LS - angled connector with nut



Connection 1
Sealing form 1
Connection 2
Sealing form 2
Design
Construction type
Construction
Norm
Material
Surface

metric nut thread
 24° outer cone
 metric cylindrical outer thread
 24° inner cone
 Adjustable direction fitting
 French series
 Angle 90°
 ISO 8434-1
 Steel
 electro galvanised

| Name | Screw | Ciśnienie | D | Budowa |
|--------------|----------|-----------|------|--------|
| VEW NW 04 HL | M 12x1,5 | 315 | 6 | L |
| VEW NW 06 HL | M 14x1,5 | 315 | 8 | L |
| VEW NW 08 HL | M 16x1,5 | 315 | 10,0 | L |
| VEW NW 10 HL | M 18x1,5 | 315 | 12 | L |
| VEW NW 13 HL | M 22x1,5 | 415 | 15,0 | L |
| VEW NW 16 HL | M 26x1,5 | 315 | 18,0 | L |
| VEW NW 20 HL | M 30x2 | 160 | 22 | L |
| VEW NW 25 HL | M 36x2 | 160 | 28,0 | L |
| VEW NW 32 HL | M 45x2 | 160 | 35,0 | L |
| VEW NW 40 HL | M 52x2 | 160 | 42 | L |
| VEW NW 03 HS | M 14x1,5 | 630 | 6 | S |
| VEW NW 04 HS | M 16x1,5 | 630 | 8 | S |
| VEW NW 06 HS | M 18x1,5 | 630 | 10,0 | S |
| VEW NW 08 HS | M 20x1,5 | 630 | 12 | S |
| VEW NW 10 HS | M 22x1,5 | 630 | 14,0 | S |
| VEW NW 13 HS | M 24x1,5 | 400 | 16 | S |
| VEW NW 16 HS | M 30x2 | 400 | 20 | S |
| VEW NW 20 HS | M 36x2 | 400 | 25 | S |
| VEW NW 25 HS | M 42x2 | 400 | 30 | S |
| VEW NW 32 HS | M 52x2 | 315 | 38 | S |