

## SF9 45 - Swage nipple, SFS-CAT angle 45°



### Application

Swage nipple for HD 100 to HD 400, KP and TE hoses

**Connection 1**  
**Sealing form 1**  
**Short code**  
**suitable for**  
**Material**  
**Surface**

SAE flange connection 6000 PSI

flat seal with SF O-ring

SFS-CAT

Caterpillar

Steel

electro galvanised

Name	DN	Size	Średnica kołnierza
PN 13 SF 9 45	13	8	31,7
PN 13 SF 9 20 45	13	8	41,3
PN 16 SF 9 13 45	16	10	31,7
PN 16 SF 9 20 45	16	10	41,3
PN 16 SF 9 25 45	16	10	47,6
PN 20 SF 9 13 45	20	12	31,7
PN 20 SF 9 45	20	12	41,3
PN 20 SF 9 25 45	20	12	47,6
PN 25 SF 9 20 45	25	16	41,3
PN 25 SF 9 45	25	16	47,6
PN 25 SF 9 32 45	25	16	54
PN 32 SF 9 25 45	32	20	47,6
PN 32 SF 9 45	32	20	54
PN 32 SF 9 40 45	32	20	63,5
PN 40 SF 9 32 45	40	24	54
PN 40 SF 9 45	40	24	63,5
PN 40 SF 9 50 45	40	24	79,4
PN 50 SF 9 40 45	50	32	63,5
PN 50 SF 9 45	50	32	79,4