



NW SW LS - angled bulkhead connector

Connection 1 + 2
Sealing form 1 + 2
Design
Construction
Standard

Included in scope of supply
Material
Surface

metric cylindrical outer thread
 24° inner cone
 Bulkhead fitting
 Angle 90°
 DIN 2353
 ISO 8434-1
 Socket with union nut and cutting ring
 Steel
 electro galvanised

Name	Screw	Ciśnienie	D	Budowa
SW NW 04 HL	M 12x1,5	315	6	L
SW NW 06 HL	M 14x1,5	315	8	L
SW NW 08 HL	M 16x1,5	315	10,0	L
SW NW 10 HL	M 18x1,5	315	12	L
SW NW 13 HL	M 22x1,5	415	15,0	L
SW NW 16 HL	M 26x1,5	315	18,0	L
SW NW 20 HL	M 30x2	160	22	L
SW NW 25 HL	M 36x2	160	28,0	L
SW NW 32 HL	M 45x2	160	35,0	L
SW NW 40 HL	M 52x2	160	42	L
SW NW 03 HS	M 14x1,5	630	6	S
SW NW 04 HS	M 16x1,5	630	8	S
SW NW 06 HS	M 18x1,5	630	10,0	S
SW NW 08 HS	M 20x1,5	630	12	S
SW NW 10 HS	M 22x1,5	630	14,0	S
SW NW 13 HS	M 24x1,5	400	16	S
SW NW 16 HS	M 30x2	400	20	S
SW NW 20 HS	M 36x2	400	25	S
SW NW 25 HS	M 42x2	400	30	S
SW NW 32 HS	M 52x2	315	38	S