



EWOM NW LS - Connection elbow metric with O-ring seal

Connection 1	metric cylindrical outer thread
Sealing form 1	Shape F
Connection 2	metric cylindrical outer thread
Sealing form 2	24° inner cone
Design	Adjustable direction screw-in fitting
Construction	Angle 90°
Included in scope of supply	Socket with union nut and cutting ring
Material	Steel
Surface	electro galvanised

Name	G1 (rys.)	G2 (rys.)	Ciśnienie	Size	Budowa
EWOM NW 04 HL	M 10x1	M 12x1,5	250	6	L
EWOM NW 06 HL	M 12x1,5	M 14x1,5	250	8	L
EWOM NW 08 HL	M 14x1,5	M 16x1,5	250	10	L
EWOM NW 10 HL	M 16x1,5	M 18x1,5	250	12	L
EWOM NW 13 HL	M 18x1,5	M 22x1,5	250	15	L
EWOM NW 16 HL	M 22x1,5	M 26x1,5	160	18	L
EWOM NW 20 HL	M 26x1,5	M 30x2	160	22	L
EWOM NW 25 HL	M 33x2	M 36x2	100	28	L
EWOM NW 32 HL	M 42x2	M 45x2	100	35	L
EWOM NW 40 HL	M 48x2	M 52x2	100	42	L
EWOM NW 03 HS	M 12x1,5	M 14x1,5	630	6	S
EWOM NW 04 HS	M 14x1,5	M 16x1,5	630	8	S
EWOM NW 06 HS	M 16x1,5	M 18x1,5	630	10	S
EWOM NW 08 HS	M 18x1,5	M 20x1,5	630	12	S
EWOM NW 10 HS	M 20x1,5	M 22x1,5	630	14	S
EWOM NW 13 HS	M 22x1,5	M 24x1,5	400	16	S
EWOM NW 16 HS	M 27x2	M 30x2	400	20	S
EWOM NW 20 HS	M 33x2	M 36x2	400	25	S
EWOM NW 25 HS	M 42x2	M 42x2	250	30	S
EWOM NW 32 HS	M 48x2	M 52x2	250	38	S