

## EWOR NW LS - Connection elbow for inch-metric with the connection inch



**Connection 1**  
**Sealing form 1**  
**Connection 2**  
**Sealing form 2**  
**Design**  
**Construction**  
**Included in scope of supply**  
**Material**  
**Surface**

BSP external thread, cylindrical form G  
 metric cylindrical outer thread  
 24° inner cone  
 Adjustable direction screw-in fitting  
 Angle 90°  
 Socket with union nut and cutting ring  
 Steel  
 electro galvanised

Name	Rura	G1 (rys.)	G2 (rys.)	Ciśnienie	Budowa
EWOR NW 04 HL	6	1/8"	M 12x1,5	250	L
EWOR NW 06 HL	8	1/4"	M 14x1,5	250	L
EWOR NW 08 HL	10	1/4"	M 16x1,5	250	L
EWOR NW 10 HL	12	3/8"	M 18x1,5	250	L
EWOR NW 13 HL	15	1/2"	M 22x1,5	250	L
EWOR NW 16 HL	18	1/2"	M 26x1,5	160	L
EWOR NW 20 HL	22	3/4"	M 30x2	160	L
EWOR NW 25 HL	28	1"	M 36x2	160	L
EWOR NW 32 HL	35	1 1/4"	M 45x2	100	L
EWOR NW 40 HL	42	1 1/2"	M 52x2	100	L
EWOR NW 03 HS	6	1/4"	M 14x1,5	630	S
EWOR NW 04 HS	8	1/4"	M 16x1,5	630	S
EWOR NW 06 HS	10	3/8"	M 18x1,5	630	S
EWOR NW 08 HS	12	3/8"	M 20x1,5	630	S
EWOR NW 10 HS	14	1/2"	M 22x1,5	630	S
EWOR NW 13 HS	16	1/2"	M 24x1,5	400	S
EWOR NW 16 HS	20	3/4"	M 30x2	400	S
EWOR NW 20 HS	25	1"	M 36x2	400	S
EWOR NW 25 HS	30	1 1/4"	M 42x2	250	S
EWOR NW 32 HS	38	1 1/2"	M 52x2	250	S