



## Sdom NW LS - Connection Banjo Metric

**Connection 1**  
**Sealing form 1**  
**Connection 2**  
**Sealing form 2**  
**Design**  
**Construction**  
**Standard**

metric cylindrical outer thread  
 Shape F  
 metric cylindrical outer thread  
 24° inner cone  
 Banjo coupling, throttle free  
 Angle 90°  
 DIN 2353  
 ISO 8434-1

**Included in scope of supply**  
**Material**  
**Surface**

Socket with union nut and cutting ring  
 Steel  
 electro galvanised

| Name          | G1 (rys.) | G2 (rys.) | Ciśnienie | Size | Budowa |
|---------------|-----------|-----------|-----------|------|--------|
| SDOM NW 04 HL | M 10x1    | M 12x1,5  | 315       | 6    | L      |
| SDOM NW 06 HL | M 12x1,5  | M 14x1,5  | 315       | 8    | L      |
| SDOM NW 08 HL | M 14x1,5  | M 16x1,5  | 315       | 10   | L      |
| SDOM NW 10 HL | M 16x1,5  | M 18x1,5  | 315       | 12   | L      |
| SDOM NW 13 HL | M 18x1,5  | M 22x1,5  | 315       | 15   | L      |
| SDOM NW 16 HL | M 22x1,5  | M 26x1,5  | 315       | 18   | L      |
| SDOM NW 20 HL | M 26x1,5  | M 30x2    | 160       | 22   | L      |
| SDOM NW 25 HL | M 33x2    | M 36x2    | 160       | 28   | L      |
| SDOM NW 32 HL | M 42x2    | M 45x2    | 160       | 35   | L      |
| SDOM NW 40 HL | M 48x2    | M 52x2    | 160       | 42   | L      |
| SDOM NW 03 HS | M 12x1,5  | M 14x1,5  | 400       | 6    | S      |
| SDOM NW 04 HS | M 14x1,5  | M 16x1,5  | 400       | 8    | S      |
| SDOM NW 06 HS | M 16x1,5  | M 18x1,5  | 400       | 10   | S      |
| SDOM NW 08 HS | M 18x1,5  | M 20x1,5  | 400       | 12   | S      |
| SDOM NW 10 HS | M 20x1,5  | M 22x1,5  | 400       | 14   | S      |
| SDOM NW 13 HS | M 22x1,5  | M 24x1,5  | 400       | 16   | S      |
| SDOM NW 16 HS | M 27x2    | M 30x2    | 400       | 20   | S      |
| SDOM NW 20 HS | M 33x2    | M 36x2    | 250       | 25   | S      |
| SDOM NW 25 HS | M 42x2    | M 42x2    | 250       | 30   | S      |
| SDOM NW 32 HS | M 48x2    | M 52x2    | 250       | 38   | S      |