

TNW LS - tee



Connection 1 - 3
Sealing form 1 - 3
Design
Construction
Standard

Included in scope of supply
Material
Surface

metric cylindrical outer thread
 24° inner cone
 Fitting
 T shaped
 DIN 2353
 ISO 8434-1
 Socket with union nut and cutting ring
 Steel
 electro galvanised

| Name | Screw | Ciśnienie | Size | Budowa |
|-----------|----------|-----------|------|--------|
| TNW 04 HL | M 12x1,5 | 315 | 6 | L |
| TNW 06 HL | M 14x1,5 | 315 | 8 | L |
| TNW 08 HL | M 16x1,5 | 315 | 10 | L |
| TNW 10 HL | M 18x1,5 | 315 | 12 | L |
| TNW 13 HL | M 22x1,5 | 315 | 15 | L |
| TNW 16 HL | M 26x1,5 | 315 | 18 | L |
| TNW 20 HL | M 30x2 | 160 | 22 | L |
| TNW 25 HL | M 36x2 | 160 | 28 | L |
| TNW 32 HL | M 45x2 | 160 | 35 | L |
| TNW 40 HL | M 52x2 | 160 | 42 | L |
| TNW 03 HS | M 14x1,5 | 630 | 6 | S |
| TNW 04 HS | M 16x1,5 | 630 | 8 | S |
| TNW 06 HS | M 18x1,5 | 630 | 10 | S |
| TNW 08 HS | M 20x1,5 | 630 | 12 | S |
| TNW 10 HS | M 22x1,5 | 630 | 14 | S |
| TNW 13 HS | M 24x1,5 | 400 | 16 | S |
| TNW 16 HS | M 30x2 | 400 | 20 | S |
| TNW 20 HS | M 36x2 | 400 | 25 | S |
| TNW 25 HS | M 45x2 | 400 | 30 | S |
| TNW 32 HS | M 52x2 | 315 | 38 | S |
| TNW 04 LL | - | - | 4 | LL |
| TNW 05 LL | - | - | 5 | LL |
| TNW 06 LL | - | - | 6 | LL |
| TNW 08 LL | - | - | 8 | LL |
| TNW 10 LL | - | - | 10 | LL |
| TNW 12 LL | - | - | 12 | LL |
| TNW 16 LL | - | - | 16 | LL |

