



Lubricating polyamide cable

The main advantage of polyamide wires is their strength, stiffness and crush and abrasion resistance (stiffer than polyurethane wires). They are commonly used in pneumatic, hydraulic, lubrication and fuel systems. Thanks to the calibration, these wires guarantee a constant full-length diameter, making them an excellent choice for plug-in connectors.

Name	Ciśn. rob. (bar)	Ciśn. rozrywające (bar)	Kolor	D2	D1
PSMARB3X0,75	33	132	naturalny	3	1,5
PSMAR4X0,85	40	120	czarny	4	2,3
PSMARB4x1	40	120	naturalny	4	2
PSMARB4x2,5	45	180	naturalny	4	2,5
PSMAR4x2,5	22	88	czarny	4	2,5
PSMAR4X1	70	280	czarny	4	2
PSMARB4x0,85	78	280	naturalny	4	2,3
PSMARB6x1	50	200	naturalny	6	4
PSMAR06	90	230	czarny	6	3
PSMARB6x1,5	33	133	naturalny	6	3
PSMARB8X1	30	120	naturalny	8	6
PSMARB8x1,5	48	193,5	naturalny	8	5
PSMAR10x6	52,5	210	czarny	10	6
PSMARB10X1	52,5	210	naturalny	10	8