



AOVM NW LS - Connection simple metric with O-ring seal

Connection 1
Sealing form 1
Connection 2
Sealing form 2
Design
Construction
Standard

metric cylindrical outer thread
 24° outer cone with O-ring
 metric nut thread
 Shape E
 Screw-in fitting
 straight
 DIN 2353
 ISO 8434-1
 Steel
 electro galvanised

Material
Surface

Name	Rura	Ciśnienie	G1	Budowa	G2
AOVM NW 04 HL	6	315	M 12x1,5	L	M 10x1
AOVM NW 06 HL	8	315	M 14x1,5	L	M 12x1,5
AOVM NW 08 HL	10	315	M 16x1,5	L	M 14x1,5
AOVM NW 10 HL	12	315	M 18x1,5	L	M 16x1,5
AOVM NW 13 HL	15	315	M 22x1,5	L	M 18x1,5
AOVM NW 16 HL	18	315	M 26x1,5	L	M 26x1,5
AOVM NW 20 HL	22	160	M 30x2	L	M 26x1,5
AOVM NW 25 HL	28	160	M 36x2	L	M 33x2
AOVM NW 32 HL	35	160	M 45x2	L	M 42x2
AOVM NW 40 HL	42	160	M 52x2	L	M 48x2
AOVM NW 03 HS	6	630	M 14x1,5	S	M 12x1,5
AOVM NW 04 HS	8	630	M 16x1,5	S	M 14x1,5
AOVM NW 06 HS	10	630	M 18x1,5	S	M 16x1,5
AOVM NW 08 HS	12	630	M 20x1,5	S	M 18x1,5
AOVM NW 10 HS	14	630	M 22x1,5	S	M 20x1,5
AOVM NW 13 HS	16	400	M 24x1,5	S	M 22x1,5
AOVM NW 16 HS	20	400	M 30x2	S	M 27x2
AOVM NW 20 HS	25	400	M 36x2	S	M 33x2
AOVM NW 25 HS	30	400	M 42x2	S	M 42x2
AOVM NW 32 HS	38	315	M 52x2	S	M 48x2