



## AOCR NW LS - simple connection for inch-metric-ring seal

**Connection 1**  
**Sealing form 1**  
**Connection 2**  
**Sealing form 2**  
**Design**  
**Construction**  
**Standard**

**Material**  
**Surface**

metric nut thread  
 24° outer cone with O-ring  
 BSP cylindrical external threads  
 Shape E  
 Screw-in fitting  
 straight  
 DIN 2353  
 ISO 8434-1  
 Steel  
 electro galvanised

Name	Rura	Ciśnienie	G1	Budowa	G2
AOCR NW 04 HL	6	315	M 12x1,5	L	1/8"
AOCR NW 06 HL	8	315	M 14x1,5	L	1/4"
AOCR NW 08 HL	10	315	M 16x1,5	L	1/4"
AOCR NW 10 HL	12	315	M 18x1,5	L	3/8"
AOCR NW 13 HL	15	315	M 22x1,5	L	1/2"
AOCR NW 16 HL	18	315	M 26x1,5	L	1/2"
AOCR NW 20 HL	22	160	M 30x2	L	3/4"
AOCR NW 25 HL	28	160	M 36x2	L	1"
AOCR NW 32 HL	35	160	M 45x2	L	1 1/4"
AOCR NW 40 HL	42	160	M 52x2	L	1 1/2"
AOCR NW 03 HS	6	400	M 14x1,5	S	1/4"
AOCR NW 04 HS	8	400	M 16x1,5	S	1/4"
AOCR NW 06 HS	10	400	M 18x1,5	S	3/8"
AOCR NW 08 HS	12	400	M 20x1,5	S	3/8"
AOCR NW 10 HS	14	400	M 22x1,5	S	1/2"
AOCR NW 13 HS	16	400	M 24x1,5	S	1/2"
AOCR NW 16 HS	20	400	M 30x2	S	3/4"
AOCR NW 20 HS	25	250	M 36x2	S	1"
AOCR NW 25 HS	30	250	M 42x2	S	1 1/4"
AOCR NW 32 HS	38	250	M 52x2	S	1 1/2"