



## CDF LS - X-piece

**Connection 1 - 4**  
**Sealing form 1 - 4**  
**Design**  
**Construction**  
**Standard**

**Included in scope of supply**  
**Material**  
**Surface**

metric cylindrical outer thread  
 24° inner cone  
 Fitting  
 K shaped  
 DIN 2353  
 ISO 8434-1  
 Socket with union nut and cutting ring  
 Steel  
 electro galvanised

Name	Screw	Ciśnienie	Budowa	G2
KNW 04 HL	M 12x1,5	315	L	6
KNW 06HL	M 14x1,5	315	L	8
KNW 08 HL	M 16x1,5	315	L	10
KNW 10 HL	M 18x1,5	315	L	12
KNW 13 HL	M 22x1,5	315	L	15
KNW 16 HL	M 26x1,5	315	L	18
KNW 20 HL	M 30x2	160	L	22
KNW 25 HL	M 36x2	160	L	28
KNW 32 HL	M 45x2	160	L	35
KNW 40 HL	M 52x2	160	L	42
KNW 03 HS	M 14x1,5	630	S	6
KNW 04 HS	M 16x1,5	630	S	8
KNW 06 HS	M 18x1,5	630	S	10
KNW 08 HS	M 20x1,5	630	S	12
KNW 10 HS	M 22x1,5	630	S	14
KNW 13 HS	M 24x1,5	400	S	16
KNW 16 HS	M 30x2	400	S	20
KNW 20 HS	M 36x2	400	S	25
KNW 25 HS	M 42x2	400	S	30
KNW 32 HS	M 52x2	315	S	38
KNW 04 LL	-	-	LL	4
KNW 05 LL	-	-	LL	5
KNW 06 LL	-	-	LL	6
KNW 08 LL	-	-	LL	8
KNW 10 LL	-	-	LL	10
KNW 12 LL	-	-	LL	12
KNW 16 LL	-	-	LL	16

