



## VLM NW - Cork

**Connection 1**  
**Sealing form 1**  
**Design**  
**Construction**  
**Standard**

**Material**

metric nut thread  
 24° outer cone with O-ring  
 Blanking nut  
 straight  
 DIN 2353  
 ISO 8434-1  
 Stainless steel

| Name      | Screw    | Ciśnienie | Budowa |
|-----------|----------|-----------|--------|
| VLM NW 04 | M 12x1,5 | 100       | L      |
| VLM NW 06 | M 14x1,5 | 400       | L      |
| VLM NW 08 | M 16x1,5 | 400       | L      |
| VLM NW 10 | M 18x1,5 | 400       | L      |
| VLM NW 13 | M 22x1,5 | 400       | L      |
| VLM NW 16 | M 26x1,5 | 315       | L      |
| VLM NW 20 | M 30x2   | 315       | L      |
| VLM NW 25 | M 36x2   | 250       | L      |
| VLM NW 32 | M 45x2   | 250       | L      |
| VLM NW 40 | M 52x2   | 250       | L      |
| VSM NW 04 | M 16x1,5 | 630       | S      |
| VSM NW 06 | M 18x1,5 | 630       | S      |
| VSM NW 08 | M 20x1,5 | 630       | S      |
| VSM NW 10 | M 22x1,5 | 630       | S      |
| VSM NW 13 | M 24x1,5 | 400       | S      |
| VSM NW 16 | M 30x2   | 400       | S      |
| VSM NW 20 | M 36x2   | 400       | S      |
| VSM NW 25 | M 45x2   | 400       | S      |
| VSM NW 32 | M 52x2   | 315       | S      |