



VEL NW LS - tee with a nut on the side

Connection 1
Sealing form 1
Connection 2 + 3
Sealing form 2 + 3
Design
Construction
Standard

metric nut thread
 Pipe socket, pre-assembled
 metric cylindrical outer thread
 24° inner cone
 Adjustable direction fitting
 L shaped
 DIN 2353
 ISO 8434-1

Included in scope of supply

Material
Surface

Socket with union nut and cutting ring
 Steel
 electro galvanised

| Name | G1 (rys.) | Ciśnienie | Size | Budowa |
|--------------|-----------|-----------|------|--------|
| VEL NW 04 HL | M 12x1,5 | 315 | 6 | L |
| VEL NW 06 HL | M 14x1,5 | 315 | 8 | L |
| VEL NW 08 HL | M 16x1,5 | 315 | 10 | L |
| VEL NW 10 HL | M 18x1,5 | 315 | 12 | L |
| VEL NW 13 HL | M 22x1,5 | 315 | 15 | L |
| VEL NW 16 HL | M 26x1,5 | 315 | 18 | L |
| VEL NW 20 HL | M 30x2 | 400 | 22 | L |
| VEL NW 25 HL | M 36x2 | 160 | 28 | L |
| VEL NW 32 HL | M 45x2 | 160 | 35 | L |
| VEL NW 40 HL | M 52x2 | 160 | 42 | L |
| VEL NW 03 HS | M 14x1,5 | 630 | 6 | S |
| VEL NW 04 HS | M 16x1,5 | 630 | 8 | S |
| VEL NW 06 HS | M 18x1,5 | 630 | 10 | S |
| VEL NW 08 HS | M 20x1,5 | 630 | 12 | S |
| VEL NW 10 HS | M 22x1,5 | 630 | 14 | S |
| VEL NW 13 HS | M 24x1,5 | 400 | 16 | S |
| VEL NW 16 HS | M 30x2 | 400 | 20 | S |
| VEL NW 20 HS | M 36x2 | 400 | 25 | S |
| VEL NW 25 HS | M 45x2 | 400 | 30 | S |
| VEL NW 32 HS | M 52x2 | 315 | 38 | S |