



## VEL NW LS - tee with a nut on the side

**Connection 1**  
**Sealing form 1**  
**Connection 2 + 3**  
**Sealing form 2 + 3**  
**Design**  
**Construction**  
**Standard**

metric nut thread  
 Pipe socket, pre-assembled  
 metric cylindrical outer thread  
 24° inner cone  
 Adjustable direction fitting  
 L shaped  
 DIN 2353  
 ISO 8434-1

**Included in scope of supply**

**Material**  
**Surface**

Socket with union nut and cutting ring  
 Steel  
 electro galvanised

Name	G1 (rys.)	Ciśnienie	Size	Budowa
VEL NW 04 HL	M 12x1,5	315	6	L
VEL NW 06 HL	M 14x1,5	315	8	L
VEL NW 08 HL	M 16x1,5	315	10	L
VEL NW 10 HL	M 18x1,5	315	12	L
VEL NW 13 HL	M 22x1,5	315	15	L
VEL NW 16 HL	M 26x1,5	315	18	L
VEL NW 20 HL	M 30x2	400	22	L
VEL NW 25 HL	M 36x2	160	28	L
VEL NW 32 HL	M 45x2	160	35	L
VEL NW 40 HL	M 52x2	160	42	L
VEL NW 03 HS	M 14x1,5	630	6	S
VEL NW 04 HS	M 16x1,5	630	8	S
VEL NW 06 HS	M 18x1,5	630	10	S
VEL NW 08 HS	M 20x1,5	630	12	S
VEL NW 10 HS	M 22x1,5	630	14	S
VEL NW 13 HS	M 24x1,5	400	16	S
VEL NW 16 HS	M 30x2	400	20	S
VEL NW 20 HS	M 36x2	400	25	S
VEL NW 25 HS	M 45x2	400	30	S
VEL NW 32 HS	M 52x2	315	38	S