



## VHL NW, VHS NW - cork

**Connection 1**  
**Sealing form 1**  
**Design**  
**Construction**  
**Standard**

metric cylindrical outer thread  
 24° inner cone  
 Blanking socket  
 straight  
 DIN 2353  
 ISO 8434-1

**Included in scope of supply**  
**Material**  
**Surface**

Socket with union nut and cutting ring  
 Steel  
 electro galvanised

Name	Screw	Ciśnienie	Budowa
VHL NW 04	M 12x1,5	100	L
VHL NW 06	M 14x1,5	400	L
VHL NW 08	M 16x1,5	400	L
VHL NW 10	M 18x1,5	400	L
VHL NW 13	M 22x1,5	400	L
VHL NW 16	M 26x1,5	315	L
VHL NW 20	M 30x2	315	L
VHL NW 25	M 36x2	250	L
VHL NW 32	M 45x2	250	L
VHL NW 40	M 52x2	250	L
VHS NW 03	M 14x1,5	630	S
VHS NW 04	M 16x1,5	630	S
VHS NW 06	M 18x1,5	630	S
VHS NW 08	M 20x1,5	630	S
VHS NW 10	M 22x1,5	630	S
VHS NW 13	M 24x1,5	400	S
VHS NW 16	M 30x2	400	S
VHS NW 20	M 36x2	400	S
VHS NW 25	M 45x2	400	S
VHS NW 32	M 52x2	315	S