



VHL NW, VHS NW - cork

Connection 1
Sealing form 1
Design
Construction
Standard

metric cylindrical outer thread
 24° inner cone
 Blanking socket
 straight
 DIN 2353
 ISO 8434-1

Included in scope of supply
Material
Surface

Socket with union nut and cutting ring
 Steel
 electro galvanised

Name	Screw	Ciśnienie	Budowa
VHL NW 04	M 12x1,5	100	L
VHL NW 06	M 14x1,5	400	L
VHL NW 08	M 16x1,5	400	L
VHL NW 10	M 18x1,5	400	L
VHL NW 13	M 22x1,5	400	L
VHL NW 16	M 26x1,5	315	L
VHL NW 20	M 30x2	315	L
VHL NW 25	M 36x2	250	L
VHL NW 32	M 45x2	250	L
VHL NW 40	M 52x2	250	L
VHS NW 03	M 14x1,5	630	S
VHS NW 04	M 16x1,5	630	S
VHS NW 06	M 18x1,5	630	S
VHS NW 08	M 20x1,5	630	S
VHS NW 10	M 22x1,5	630	S
VHS NW 13	M 24x1,5	400	S
VHS NW 16	M 30x2	400	S
VHS NW 20	M 36x2	400	S
VHS NW 25	M 45x2	400	S
VHS NW 32	M 52x2	315	S