

Fuel dispensing hose



Designed for dispensing petroleum-based fuels with aromatic content up to 50%, including bioethanol (fuel containing oxygen compounds up to a maximum of 15%) and biodiesel (80% diesel and 20% bio-ester) fuel supplier to the tanks of motor vehicles, excluding liquid gas (LPG), temp. -40 ° C to + 55 ° C, a layer ext.: rubber, NBR / PVC, black, smooth, resistant to fuels, reinforcement: textile, wrapped and two crossing links Copper layer ext.: rubber, CR, black with cloth impression, resistant to: fuels, abrasion and weathering, retain high flexibility in positive and negative temperatures, resistance: max 1x106 Ω / m, we can provide in the form of finished cables.

Name	Średnica wew. [mm]	Średnica zew. [mm]	Ciśnienie pracy MPa	Ciśn. rozrywające MPa	Długość max m
FI 16 TŁ PALIWO	16	26	1,6	4,8	40
FI 19 TŁ PALIWO	19	31	1,6	4,8	40
FI 20 TŁ PALIWO	20	32	1,6	4,8	40
FI 25 TŁ PALIWO	25	37	1,6	4,8	40
FI 32 TŁ PALIWO	31,5	43,5	1,6	4	40
FI 38 TŁ PALIWO	38	53	1,6	4,8	20
FI 40 TŁ PALIWO	40	55	1,6	4,8	20
FI 50 TŁ PALIWO	50	65	1,6	4,8	20