

Suction hose for foodstuffs



High-quality, durable hose designed for suction and discharge of liquid foodstuffs vacuum to 0.063 MPa; used as conduits for liquid foodstuffs such as drinking water, milk, dairy products, juices, musts, beverages with an alcohol content: blue (concentration max 40%), white (concentration max 40%), red (concentration max 96%) and acidic foods having a pH of $\leq 4,5$, temp. -30°C to $+70^{\circ}\text{C}$, periodically to 140°C during the washing hose with hot water or steam, a layer ext.: rubber, EPDM, white, smooth, reinforcement: textile and steel wire helix, layer outer.: rubber, EPDM / SBR, blue, red or white with cloth impression. This hose meets the requirements of NIH, FDA, BGVV and a recognition of the major manufacturers of food products.

Name	Średnica wew. [mm]	Ciśnienie pracy MPa	Ciśn. rozrywające MPa	Długość max m	Grubość ścianki mm
FI 20 SS-TŁ SPOŻ	20	2	6	20	6
FI 25 SS-TŁ SPOŻ	25	2	6	20	6
FI 32 SS-TŁ SPOŻ	31,5	1,5	4,5	20	6,5
FI 35 SS-TŁ SPOŻ	35	1,2	3,6	20	6,5
FI 38 SS-TŁ SPOŻ	38	1,2	3,6	20	6,5
FI 40 SS-TŁ SPOŻ	40	1,2	3,6	20	6,5
FI 45 SS-TŁ SPOŻ	45	1	3	20	6,5
FI 50 SS-TŁ SPOŻ	50	1	3	20	6,5
FI 63 SS-TŁ SPOŻ	63	0,7	2,1	10	7,5
FI 70 SS-TŁ SPOŻ	70	0,7	2,1	10	7,5
FI 75 SS-TŁ SPOŻ	75	0,7	2,1	10	7,5
FI 80 SS-TŁ SPOŻ	80	0,7	2,1	10	7,5
FI 90 SS-TŁ SPOŻ	90	0,5	1,5	10	7,5
FI 100 SS-TŁ SPOŻ	100	0,5	1,5	10	7,5
FI 110 SS-TŁ SPOŻ	110	0,5	1,5	10	7,5
FI 125 SS-TŁ SPOŻ	125	0,4	1,2	10	8
FI 150 SS-TŁ SPOŻ	150	0,3	0,9	10	8
FI 200 SS-TŁ SPOŻ	200	0,3	0,9	6	9
FI 250 SS-TŁ SPOŻ	250	0,2	0,6	6	10