

Suction and discharge hose for steam 165C



High-quality, durable hose designed for suction and pressure saturated steam of low pressure 0.063 MPa pressure of 0,6 MPa and temperature. 165 ° C, used as a conduit for the flow of hot water and saturated steam in industrial, ext. : rubber layer, EPDM, black, reinforcement: textile and one or two steel wire coils, outer layer of : rubber, EPDM, black, resistant to atmospheric factors, high fatigue strength provides long service life of the hose.

Name	Średnica wew. [mm]	Ciśnienie pracy MPa	Ciśn. rozrywające MPa	Długość max m	Grubość ścianki mm
FI 20 SS-TŁ PARA165	20	0,6	6	20	6
FI 45 SS-TŁ PARA165	45	0,6	6	20	8
FI 50 SS-TŁ PARA165	50	0,6	6	20	8
FI 63 SS-TŁ PARA165	63	0,6	6	10	8,5
FI 70 SS-TŁ PARA165	70	0,6	6	10	8,5
FI 75 SS-TŁ PARA165	75	0,6	6	10	8,5
FI 80 SS-TŁ PARA165	80	0,6	6	10	8,5
FI 90 SS-TŁ PARA165	90	0,6	6	10	8,5
FI 100 SS-TŁ PARA165	100	0,6	6	10	10
FI 25 SS-TŁ PARA165	25	0,6	6	20	7,5
FI 32 SS-TŁ PARA165	31,5	0,6	6	20	6,5
FI 35 SS-TŁ PARA165	35	0,6	6	20	8
FI 38 SS-TŁ PARA165	38	0,6	6	20	8
FI 40 SS-TŁ PARA165	40	0,6	6	20	8