

## Hose for plastering



Strong, durable and highly resistant to abrasion and difficult working conditions snake thick-walled, used in construction and quarries, designed for pumping mortars, temp.: From -35 ° C to + 60 ° C, a layer ext.: rubber, SBR, black, smooth, abrasion up to 70mm<sup>3</sup> or 40mm<sup>3</sup> max, reinforcement: textile layer ext.: rubber, EPDM / SBR, black with cloth impression, resistant to atmospheric agents.

| Name          | Średnica wew. [mm] | Ciśnienie pracy MPa | Ciśn. rozrywające MPa | Długość max m | Grubość ścianki mm |
|---------------|--------------------|---------------------|-----------------------|---------------|--------------------|
| FI 25 Tł Tynk | 25                 | 1,6                 | 4,5                   | 40            | 5,8                |
| FI 60 Tł Tynk | 60                 | 1,6                 | 4,5                   | 10            | 9,5                |
| FI 63 Tł Tynk | 63                 | 1,6                 | 4,5                   | 10            | 9,5                |
| FI 32 Tł Tynk | 31,5               | 4                   | 12                    | 40            | 9,5                |
| FI 40 Tł Tynk | 40                 | 4                   | 12                    | 20            | 10,5               |
| FI 50 Tł Tynk | 50                 | 4                   | 12                    | 20            | 10,5               |