

GMM 63 Pressure gauge connection bottom



Gauges Glycerine (Ø63) with radial connection, a pressure of up to -1 MPa ~ 100 MPa. Particularly robust, used for pumps, compressors, power supplies, hydraulic systems, high uzdatniaczach water cooling systems

Name	Gwint BSP	Średnica	Zakres ciśnień
GMM63 -1/0	1/4"	63	-1 / 0,0 bar
GMM63-0/1	1/4"	63	0 - 1,0 bar
GMM63-0/1,6	1/4"	63	0 - 1,6 bar
GMM63 -1/1,5	1/4"	63	-1 / +1,5 bar
GMM63 -1/3	1/4"	63	-1 / +3,0 bar
GMM63 -1/5	1/4"	63	-1 / +5,0 bar
GMM63 -1/9	1/4"	63	-1 / +9,0 bar
GMM63-0/4	1/4"	63	0 - 4,0 bar
GMM63-06	1/4"	63	0 - 6,0 bar
GMM63-10	1/4"	63	0 - 10,0 bar
GMM63-16	1/4"	63	0 - 16,0 bar
GMM63-25	1/4"	63	0 - 25,0 bar
GMM63-40	1/4"	63	0 - 40,0 bar
GMM63-60	1/4"	63	0 - 60,0 bar
GMM63-80	1/4"	63	0 - 80,0 bar
GMM63-100	1/4"	63	0 - 100,0 bar
GMM63-160	1/4"	63	0 - 160,0 bar
GMM63-250	1/4"	63	0 - 250,0 bar
GMM63-315	1/4"	63	0 - 315,0 bar
GMM63-400	1/4"	63	0 - 400,0 bar
GMM63-600	1/4"	63	0 - 600,0 bar
GMM63-1000	1/4"	63	0 - 1000,0 bar