



GMM 63 H Pressure gauge rear connection

Gauges Glycerine (Ø63) with a connection back centric, with a pressure of up to -1 MPa ~ 100 MPa. Particularly robust, used for pumps, compressors, power supplies, hydraulic systems, high uzdatniaczach water cooling systems

Name	Gwint BSP	Średnica	Zakres ciśnień
GMM63 -1/0 H	1/4"	63	-1 / 0,0 bar
GMM63-0/1 H	1/4"	63	0 - 1,0 bar
GMM63-0/1,6 H	1/4"	63	0 - 1,6 bar
GMM63 -1/1,5 H	1/4"	63	-1 / +1,5 bar
GMM63 -1/3 H	1/4"	63	-1 / +3,0 bar
GMM63 -1/5 H	1/4"	63	-1 / +5,0 bar
GMM63 -1/9 H	1/4"	63	-1 / +9,0 bar
GMM63-0/4 H	1/4"	63	0 - 4,0 bar
GMM63-06 H	1/4"	63	0 - 6,0 bar
GMM63-10 H	1/4"	63	0 - 10,0 bar
GMM63-16 H	1/4"	63	0 - 16,0 bar
GMM63-25 H	1/4"	63	0 - 25,0 bar
GMM63-40 H	1/4"	63	0 - 40,0 bar
GMM63-60 H	1/4"	63	0 - 60,0 bar
GMM63-80 H	1/4"	63	0 - 80,0 bar
GMM63-100 H	1/4"	63	0 - 100,0 bar
GMM63-160 H	1/4"	63	0 - 160,0 bar
GMM63-250 H	1/4"	63	0 - 250,0 bar
GMM63-315 H	1/4"	63	0 - 315,0 bar
GMM63-400 H	1/4"	63	0 - 400,0 bar
GMM63-600 H	1/4"	63	0 - 600,0 bar
GMM63-1000 H	1/4"	63	0 - 1000,0 bar