

Gland packing PES-PES / K



PSE gland, compact, single-acting. Specially designed profile makes the package is doing very well in equipment exposed to shock, vibration and high pressure. PSE consists of 3 parts: the main seal is made of NBR, from below is a fabric reinforced support ring with a correspondingly profiled inner groove in which is mounted a ring polyacetal anti-implosion, ensures optimum sealing, especially in high vibration.

PES / K - special version of PES, the main seal NBR has a profile used in mining machinery.

Type	Pressure [bar]	Speed [m / s]	Temperature [° C]	Stuff	Resistance Media	Equivalent seals
PSE PES / K	700	0.5	-30 110	NBR + fabric + POM	> Hydraulic oils > Water > emulsions	K34, MGM, SM RCK .. AG

Name	d (rys.)	D (rys.)	H (rys.)	M (rys.)
PSE-701	15	27	20	15,40
PSE-702	20	33	20	20,40
PSE-703	22	35	20	22,40
PSE-704	25	38	20	25,40
PSE-705	28	41	20	28,40
PSE-706	30	43	20	30,40
PSE-707	32	47	22,50	32,40
PSE-708	35	45	25,59	35,40
PSE-709	35	47	22,50	35,40
PSE-710	35	50	22,50	35,40
PSE-711	40	50	17,50	40,40
PSE-713	40	52	22,50	40,40
PSE-714	40	55	22,62	40,40
PSE-715	40	60	30	40,40
PSE-716	45	60	22,50	45,40
PSE-717	45	65	28	45,40
PSE-718	50	63	20	50,40
PSE-719	50	65	24,50	50,40
PSE-720	50	65	22,50	50,40
PSE-721	50	70	3	50,40
PSE-722	50	70	31,90	50,40
PSE-723	55	70	25	55,40
PSE-724	55	70	22,50	55,40

Name	d (rys.)	D (rys.)	H (rys.)	M (rys.)
PSE-725	55	75	32	55,40
PSE-726	55	75	30	55,40
PSE-726/1	56	71	22,50	56,40
PSE-727	56	71	25	56,40
PSE-728	56	76	28	56,40
PSE-729	60	75	25	60,40
PSE-730	60	75	22,50	60,40
PSE-731	60	77	27	60,40
PSE-731/1	60	80	27	60,40
PSE-731/2	60	80	30	60,40
PSE-732	60	80	34,90	60,40
PSE-733	60	80	32	60,40
PSE-734	63	83	30	63,40
PSE-735	63	83	29	63,40
PSE-736	63	83	27	63,40
PSE-737	65	85	29	65,40
PSE-738	70	85	22,50	70,40
PSE-739/1	70	90	30	70,40
PSE-740	70	90	31,90	70,40
PSE-741	75	95	28	75,40
PSE-742	75	95	30	75,40
PSE-743	76,50	96,50	32,50	76,90
PSE-744	80	100	30	80,40
PSE-745	85	105	30	85,40
PSE-745/1	90	105	22,50	90,40
PSE-746	90	105	25	90,40
PSE-747	90	105	33,53	90,40
PSE-748	90	110	30	90,40
PSE-750	95	115	28	95,40
PSE-751	100	114,30	24	100,40
PSE-752	100	120	30	100,40
PSE-755	105	125	30	105,40
PSE-756	110	130	32,50	110,40
PSE-756/1	110	132	36,50	110,40
PSE-757	115	130	30	115,70
PSE-758	120	140	30	120,70
PSE-759	125	145	29,62	125,70
PSE-760	130	150	28	130,70
PSE-761/1	140	160	19	140,70
PSE-762	140	160	28	140,70
PSE-763	140	160	30	140,70
PSE-764	150	170	28	150,70
PSE-766	160	180	28	160,70
PSEK-903	70	85	22,50	70,40
PSEK-905	80	95	22,50	80,40
PSEK-907	85	100	22,50	85,40
PSEK-908/1	90	105	22,50	90,40

Name	d (rys.)	D (rys.)	H (rys.)	M (rys.)
PSEK-909	95	110	22,50	95,40
PSEK-909/1	100	115	22,50	100,40
PSEK-910	110	125	22,50	110,40
PSEK-911	115	130	22,50	115,70
PSEK-913	120	135	22,50	120,70
PSEK-915	125	140	22,50	125,70
PSEK-918	140	155	22,50	140,70
PSEK-919	140	160	22,50	140,70