

Gland packing TGO



TGO is recommended to seal cylinders of medium and high pressure. One-piece. Rubber blend fabric provides excellent wear resistance and minimizes the effect of wiping.

| Type | Pressure [bar] | Speed [m / s] | Temperature [° C] | Stuff | Resistance Media | Equivalent seals |
|------|----------------|---------------|-------------------|--------------|--------------------------------------------|------------------|
| TGO | 250 | 0.5 | -30 120 | NBR + fabric | > Hydraulic oils > Water > emulsions | - |

| Name | d (rys.) | D (rys.) | H (rys.) |
|----------|----------|----------|----------|
| TGO-2504 | 10 | 17 | 6,40 |
| TGO-2505 | 12 | 19 | 6,40 |
| TGO-2506 | 14 | 22 | 6,40 |
| TGO-2508 | 16 | 24 | 6,40 |
| TGO-2509 | 18 | 26 | 6,40 |
| TGO-2510 | 20 | 28 | 6,40 |
| TGO-2511 | 22 | 30 | 6,40 |
| TGO-2512 | 25 | 33 | 6,40 |
| TGO-2513 | 28 | 36 | 6,40 |
| TGO-2514 | 30 | 38 | 6,40 |
| TGO-2515 | 32 | 40 | 6,40 |
| TGO-2516 | 35 | 43 | 6,40 |
| TGO-2517 | 36 | 44 | 6,40 |
| TGO-2518 | 40 | 48 | 6,40 |
| TGO-2519 | 42 | 50 | 6,40 |
| TGO-2520 | 45 | 55 | 8 |
| TGO-2521 | 50 | 60 | 8 |
| TGO-2522 | 55 | 65 | 8 |
| TGO-2523 | 56 | 66 | 8 |
| TGO-2524 | 60 | 70 | 8 |
| TGO-2525 | 63 | 75 | 9,60 |
| TGO-2526 | 65 | 77 | 9,60 |
| TGO-2527 | 70 | 82 | 9,60 |
| TGO-2528 | 75 | 87 | 9,60 |
| TGO-2529 | 80 | 92 | 9,60 |
| TGO-2530 | 85 | 97 | 9,60 |
| TGO-2531 | 90 | 102 | 9,60 |

| Name | d (rys.) | D (rys.) | H (rys.) |
|-------------|-----------------|-----------------|-----------------|
| TGO-2532 | 100 | 115 | 12 |
| TGO-2533 | 110 | 125 | 12 |
| TGO-2534 | 115 | 130 | 12 |
| TGO-2535 | 125 | 140 | 12 |
| TGO-2536 | 140 | 160 | 16 |
| TGO-2537 | 150 | 170 | 16 |
| TGO-2538 | 160 | 180 | 16 |
| TGO-2539 | 180 | 200 | 16 |
| TGO-2540 | 200 | 220 | 16 |