

Gland packing TGO



TGO is recommended to seal cylinders of medium and high pressure. One-piece. Rubber blend fabric provides excellent wear resistance and minimizes the effect of wiping.

Type	Pressure [bar]	Speed [m / s]	Temperature [° C]	Stuff	Resistance Media	Equivalent seals
TGO	250	0.5	-30 120	NBR + fabric	> Hydraulic oils > Water > emulsions	-

Name	d (rys.)	D (rys.)	H (rys.)
TGO-2504	10	17	6,40
TGO-2505	12	19	6,40
TGO-2506	14	22	6,40
TGO-2508	16	24	6,40
TGO-2509	18	26	6,40
TGO-2510	20	28	6,40
TGO-2511	22	30	6,40
TGO-2512	25	33	6,40
TGO-2513	28	36	6,40
TGO-2514	30	38	6,40
TGO-2515	32	40	6,40
TGO-2516	35	43	6,40
TGO-2517	36	44	6,40
TGO-2518	40	48	6,40
TGO-2519	42	50	6,40
TGO-2520	45	55	8
TGO-2521	50	60	8
TGO-2522	55	65	8
TGO-2523	56	66	8
TGO-2524	60	70	8
TGO-2525	63	75	9,60
TGO-2526	65	77	9,60
TGO-2527	70	82	9,60
TGO-2528	75	87	9,60
TGO-2529	80	92	9,60
TGO-2530	85	97	9,60
TGO-2531	90	102	9,60

Name	d (rys.)	D (rys.)	H (rys.)
TGO-2532	100	115	12
TGO-2533	110	125	12
TGO-2534	115	130	12
TGO-2535	125	140	12
TGO-2536	140	160	16
TGO-2537	150	170	16
TGO-2538	160	180	16
TGO-2539	180	200	16
TGO-2540	200	220	16