

Seal Piston CUT



CUT two-piece seal set, double action. Designed for heavy hydraulic applications. Outdoor cut guide ring is made of polyamide, inside, a pressing element is a rubber profile with a square cross-section. An additional function of the ring NBR is holding static seals in the groove.

Type	Pressure [bar]	Speed [m / s]	Temperature [° C]	Stuff	Resistance Media	Equivalent seals
CUT	500	1	-30 110	NBR + polyamide	> Hydraulic oils > Water > emulsions	TUT, OMC-S OKAY

Name	d (rys.)	D (rys.)	H (rys.)
CUT63-47,5-6,3	47,50	63	6,30
CUT75-59,5-6,3	59,50	75	6,30
CUT80-64,5-6,3	64,50	80	6,30
CUT90-69-8,1	69	90	8,10
CUT100-79-8,1	79	100	8,10
CUT100-84,5-6,3	84,50	100	6,30
CUT110-89-8,1	89	110	8,10
CUT115-94-8,1	94	115	8,10
CUT120-99-8,1	99	120	8,10
CUT125-104-8,1	104	125	8,10
CUT130-109-8,1	109	130	8,10
CUT140-119-8,1	119	140	8,10
CUT150-129-8,1	129	150	8,10
CUT160-139-8,1	139	160	8,10
CUT170-149-8,1	149	170	8,10
CUT180-159-8,1	159	180	8,10
CUT190-169-8,1	169	190	8,10
CUT200-179-8,1	179	200	8,10
CUT220-199-8,1	199	220	8,10
CUT230-209-8,1	209	230	8,10
CUT250-229-8,1	229	250	8,10