



## TF guide rings

**PTFE + BR** Teflon tape is characterized by low friction, resistance to chemicals, temperature and excessive wear. This reduces the effect of "stick-slip". Suitable for industrial hydraulics, water, food, pneumatics.

Type	Speed [m / s]	Temperature [° C]	Stuff	Resistance Media	Equivalent seals
PTFE + BR	15	-100 +250	PTFE + Bronze 40%	> Hydraulic oils > Water > Emulsions > Hydrocarbons > Chlorine > Esters	FB ATS-N, SB FUB01, PBS

Name	h (rys.)	H (rys.)	S
TF-150030	3	3,20	1,50
TF-150042	4	4,20	1,50
TF-150063	6,10	6,30	1,50
TF-200063	6,10	6,30	2
TF-20097	9,50	9,70	2
TF-200150	14,80	15	2
TF-200200	19,50	20	2
TF-250057	5,50	5,70	2,50
TF-250063	6,10	6,30	2,50
TF-250097	9,50	9,70	2,50
TF-250150	2,50	14,80	15
TF-250200	2,50	19,50	20
TF-250250	2,50	24,50	25
TF-250300	2,50	29,50	30
TF-300097	3	9,50	9,70
TF-300150	3	14,80	15
TF-300200	3	19,50	20
TF-300250	3	24,50	25
TF-300300	3	29,50	30
TF-400097	4	9,50	9,70
TF-400150	4	14,80	15
TF-400200	4	19,50	20
TF-400250	4	24,50	25