

## Scraper seal Stock Exchange



**WSE** is a ring sealing - scraper. Made of sturdy polyurethane Tecnolan. The main feature of the scraper is to protect the piston rod against dirt, dust and particles of metal, the presence of the second lip ensures a perfect seal even when small leak. WSE profile is recommended mainly for industrial cylinders and equipment to move earth masses.

Type	Pressure [bar]	Speed [m / s]	Temperature [° C]	Stuff	Resistance Media	Equivalent seals
Warsaw Stock Exchange	-	-	-40 110	Polyurethane Tecnolan	mud, dust, oil, water, emulsions	WD17, P8

Name	d (rys.)	D (rys.)	h (rys.)	H (rys.)
GPW-012	12	20	4	8
GPW-014	14	22	4	8
GPW-016	16	24	4	8
GPW-018	18	26	4	8
GPW-020	20	28	4	8
GPW-022	22	30	4	8
GPW-025	25	33	4	8
GPW-028	28	36	4	8
GPW-030	30	38	4	8
GPW-032	32	40	4	8
GPW-035	35	43	4	8
GPW-036	36	44	4	8
GPW-038	38	46	4	8
GPW-040	40	48	4	8
GPW-045	45	53	4	8
GPW-050	50	58	4	8
GPW-055	55	63	4	8
GPW-056	56	64	4	8
GPW-060	60	68	4	8
GPW-063	63	71	4	8
GPW-070	70	78	4	8
GPW-075	75	83	4	8
GPW-080	80	88	4	8
GPW-085	85	93	4	8
GPW-090	90	98	4	8
GPW-100	100	108	4	8
GPW-110	110	122	5,50	11

<b>Name</b>	<b>d (rys.)</b>	<b>D (rys.)</b>	<b>h (rys.)</b>	<b>H (rys.)</b>
GPW-115	115	127	5,50	11
GPW-120	120	132	5,50	11
GPW-125	125	137	5,50	11
GPW-130	130	142	5,50	11
GPW-135	135	147	5,50	11
GPW-140	140	152	5,50	11
GPW-150	150	162	5,50	11
GPW-160	160	172	5,50	11
GPW-170	170	182	5,50	11
GPW-180	180	192	5,50	11