

Scraper seal GHW



GHW is a ring sealing - scraper. Made of sturdy polyurethane Tecnolan. The main feature of the scraper is to protect the piston rod against dirt, dust and particles of metal, the presence of the second lip ensures a perfect seal even when small leak. GHW profile is recommended mainly for industrial cylinders and equipment to move earth masses.

Type	Pressure [bar]	Speed [m / s]	Temperature [° C]	Stuff	Resistance Media	Equivalent seals
GHW	-	-	-40 110	Polyurethane Tecnolan	mud, dust, oil, water, emulsions	K27, WD22 .. RSW, P9, AD48

Name	d (rys.)	D (rys.)	H (rys.)	M (rys.)
GHW-012	12	18,60	3,80	15
GHW-014	14	20,60	3,80	17
GHW-018	18	24,60	3,80	21
GHW-020	20	28,60	5,30	23
GHW-020/1	20	26,60	3,80	23
GHW-022	22	30,60	5,30	25
GHW-025	25	33,60	5,30	28
GHW-028	28	36,60	5,30	31
GHW-030	30	38,60	5,30	33
GHW-032	32	40,60	5,30	35
GHW-035	35	43,60	5,30	38
GHW-036	36	44,60	5,30	39
GHW-040	40	48,60	5,30	43
GHW-042	42	50	5,30	45
GHW-045	45	53,60	5,30	48
GHW-050	50	58,60	5,30	53
GHW-055	55	63,60	5,30	58
GHW-056	56	64,60	5,30	59
GHW-060	60	68,60	5,30	63
GHW-063	63	71,60	5,30	66
GHW-065	65	73,60	5,30	68
GHW-070	70	78,60	5,30	73
GHW-075	75	83,60	5,30	78
GHW-080	80	88,60	5,30	83
GHW-080/1	80	92	7,10	86
GHW-085	85	97,20	7,10	91
GHW-090	90	102,20	7,10	96

Name	d (rys.)	D (rys.)	H (rys.)	M (rys.)
GHW-100	100	112,20	7,10	106
GHW-110	110	122,20	7,10	116
GHW-120	120	132,20	7,10	126
GHW-130	130	142,20	7,10	136
GHW-135	135	147,20	7,10	141