



Static seal PPM

Material: Steel Soft + NBR 70

Operating temperature: -30 °C + 110 °C

Name	D	Średnica	A	B	C	E	F	ilość szt. w opakowaniu
606-PPM-12	0,30	M6	10	8	6,70	1,00	4,70	100
612-PPM-08	0,30	M8	13	10	8,70	1,00	6,40	100
617-PPM-10	0,40	M10	16	12,40	10,70	1,50	8,05	100
622-PPM-12	0,40	M12	18	14,30	12,70	1,50	9,73	100
627-PPM-14	0,40	M14	22	16,40	14,70	1,50	11,38	100
629-PPM-16	0,40	M16	24	18,40	16,70	1,50	13,41	100
632-PPM-18	0,40	M18	26	20,40	18,70	1,50	14,76	100
633-PPM-20	0,40	M20	28	22,50	20,70	1,50	16,76	100
636-PPM-22	0,40	M22	30	24,40	22,70	2,00	18,74	100
638-PPM-24	0,40	M24	32	26,40	24,70	2,00	20,11	100
640-PPM-27	0,40	M27	36	29	27,20	2,00	23,30	100
642-PPM-30	0,40	M30	39	33	31,00	2,00	25,70	100
643-PPM-33	0,40	M33	42	35,80	33,70	2,00	28,70	100
645-PPM-36	0,40	M36	46	38,80	36,70	2,00	31,10	100
647-PPM-42	0,40	M42	53	44,40	42,70	3,00	36,50	100
820-PP45-A	0,25/0,51	1/8"	15,88	11,84	10,37	2,03	8,56	100
821-PP45-B	0,25/0,51	1/4"	20,57	15,21	13,74	2,03	11,45	100
823-PP45-C	0,25/0,51	3/8"	23,80	18,75	17,28	2,03	14,96	100
825-PP45-D	0,25/0,51	1/2"	28,58	23,01	21,54	2,49	18,64	100
826-PP45-E	0,25/0,51	5/8"	31,75	24,97	23,49	2,49	20,60	100
827-PP45-F	0,25/0,51	3/4"	34,93	28,53	27,05	2,49	24,13	100
830-PP45-H	0,25/0,51	1"	42,80	36,88	33,89	3,20	30,30	100
832-PP45-J	0,25/0,51	1.1/4"	52,38	45,93	42,93	3,20	38,96	100
833-PP45-K	0,25/0,51	1.1/2"	58,60	51,39	48,44	3,20	44,86	100
836-PP45-M	0,25/0,51	2"	73,03	63,63	60,58	3,20	56,67	50
XV821-PP45-B	0,25/0,51	1/4"	20,57	15,21	13,74	2,03	11,45	-
XV823-PP45-C	0,25/0,51	3/8"	23,80	18,75	17,28	2,03	14,96	-
XV825-PP45-D	0,25/0,51	1/2"	28,58	23,01	21,54	2,49	18,64	-

Name	D	Średnica	A	B	C	E	F	ilość szt. w opakowaniu
XV827-PP45-F	0,25/0,51	3/4"	34,93	28,53	27,05	2,49	24,13	-
XV830-PP45-H	0,25/0,51	1"	42,80	36,88	33,89	3,00	30,30	-