



XSVR ED - Bulkhead screw-in fitting

Connection 1
Sealing form 1
Connection 2
Sealing form 2
Design
Construction
Standard

Included in scope of supply
Material
Surface

BSP external thread, cylindrical
 Shape E
 metric cylindrical outer thread
 24° inner cone
 Bulkhead screw-in fitting
 straight
 DIN 2353
 ISO 8434-1
 Socket (without union nut and cutting ring)
 Steel
 electro galvanised

Name	G1 (rys.)	G2 (rys.)	Ciśnienie	L1 (mm)	S1	L2 (mm)	Typoszer eg	Ø D2 (mm)	D3 (mm)	i (mm)	SW	G2
SVR NW 25 HS ED	1.1/4" -11	M 42 x 2	160	89	50	37,5	S	30	49,9	20,0	50	
SVR NW 16 HL 3/4 ED	3/4" -14	M 26 x1,5	250	68	36	33,5	L	18	31,9	20,0	32	
SVR NW 20 HS ED	1" -11	M 36x2	250	82	46	35	S	25	39,9	18	46	
SVR NW 20 HS 3/4 ED	3/4" -14	M 36 x 2	250	80	46	35	S	25	31,9	16	46	
SVR NW 40 HL ED	1.1/2" -11	M 52 x 2	250	86	65	36	L	42	54,9	22	60	
SVR NW 20 HL ED	3/4" -14	M 30x2	250	71	41	34,5	L	22	31,9	16	36	
SVR NW 16 HL 1 ED	1" -11	M 26 x1,5	250	73	36	33,5	L	18	39,9	18	41	
SVR NW 13 HL ED	1/2" -14	M 22x1,5	250	62	32	31,0	L	10	26,9	14	27	
SVR NW 13 HL 3/4 ED	3/4" -14	M 22x1,5	250	66	32	31,0	L	15	31,9	16	32	
SVR NW 16 HL ED	1/2" -14	M 26x1,5	250	66	36	33,5	L	18	26,9	14	32	
SVR NW 06 HL 3/8 ED	3/8" -19	M 14x1,5	315	54,5	19	27	L	8	21,9	12	22	
SVR NW 06 HL ED	1/4" -19	M 14x1,5	315	53,0	19	27	L	8	18,9	12	19	
SVR NW 10 HL ED	3/8" -19	M 18x1,5	315	56,5	24	29	L	12	21,9	12	24	
SVR NW 08 HL 1/2 ED	1/2" -14	M 16x1,5	315	59	22	27	L	10	26,9	14	27	
SVR NW 06 HL 1/2 ED	1/2" -14	M 14x1,5	315	58	19	27	L	8	26,9	14	27	
SVR NW 10 HL 1/2 ED	1/2" -14	315	M 18x1,5	60	24	29	L	12	26,9	14	27	
SVR NW 08 HL ED	1/4" -19	M 16x1,5	315	55,0	22	28,0	L	10	18,9	12	22	

Name	G1 (rys.)	G2 (rys.)	Ciśnienie	L1 (mm)	S1	L2 (mm)	Typoszer eg	Ø D2 (mm)	D3 (mm)	i (mm)	SW	G2
SVR NW 16 HS ED	3/4" -14	M 30 x 2	400	75	41	33,5	L	20	31,9	16	41	
SVR NW 13 HS 3/4 ED	3/4" -14	M 24x1,5	400	70	32	31,5	S	16	31,9	16	32	
SVR NW 08 HS 1/2 ED	1/2" -14	M 20x1,5	400	65	27	30,5	S	12	26,9	14	27	
SVR NW 13 HS ED	1/2" -14	M 24x1,5	400	68	32	31,5	S	16	26,9	14	32	