



## GE HB HN Screw-in sockets

Connection 1	BSP external thread, cylindrical
Sealing form 1	60° inner cone
Connection 2	NPT external threads
Sealing form 2	thread seal
Design	Screw-in sockets
Construction	straight
Material	Steel
Surface	electro galvanised

Name	G1	G2
GE HB 02 HN	1/8	1/8
GE HB 02 HN 04	1/8	1/4
GE HB 04 HN 02	1/4	1/8
GE HB 04 HN	1/4	1/4
GE HB 04 HN 06	1/4	3/8
GE HB 04 HN 08	1/4	1/2
GE HB 04 HN 12	1/4	3/4
GE HB 06 HN 02	3/8	1/8
GE HB 06 HN 04	3/8	1/4
GE HB 06 HN	3/8	3/8
GE HB 06 HN 08	3/8	1/2
GE HB 06 HN 12	3/8	3/4
GE HB 06 HN 16	3/8	1
GE HB 08 HN 04	1/2	1/4
GE HB 08 HN 06	1/2	3/8
GE HB 08 HN	1/2	1/2
GE HB 08 HN 12	1/2	3/8
GE HB 08 HN 16	1/2	1
GE HB 10 HN 08	5/8	1/2
GE HB 10 HN 12	5/8	3/4
GE HB 12 HN 04	3/4	1/4
GE HB 12 HN 06	3/4	3/8
GE HB 12 HN 08	3/4	1/2
GE HB 12 HN	3/4	3/4
GE HB 12 HN 16	3/4	1
GE HB 12 HN 20	3/4	1 1/4
GE HB 16 HN 08	1	1/2
GE HB 16 HN 12	1	3/4

<b>Name</b>	<b>G1</b>	<b>G2</b>
GE HB 16 HN	1	1
GE HB 16 HN 20	1	1 1/4
GE HB 16 HN 24	1	1 1/2
GE HB 16 HN 32	1	2
GE HB 20 HN 12	1,1/4	3/4
GE HB 20 HN 16	1,1/4	1
GE HB 20 HN	1,1/4	1,1/4
GE HB 20 HN 24	1,1/4	1 1/2
GE HB 24 HN 16	1,1/2	1
GE HB 24 HN 20	1,1/2	1,1/4
GE HB 24 HN	1,1/2	1,1/2
GE HB 24 HN 32	1,1/2	2
GE HB 32 HN 20	2	1,1/4
GE HB 32 HN 24	2	1 1/2
GE HB 32 HN	2	2