



## GE HMOK HB Screw-in sockets

Connection 1  
Sealing form 1

Connection 2  
Sealing form 2

Design  
Construction  
Material  
Surface

metric cylindrical outer thread  
Thread socket with O-ring + spacer  
diaphragm ring  
BSP cylindrical external threads  
60° inner cone  
Screw-in sockets  
straight  
Steel  
electro galvanised

Name	G1	G2
GE HMOK 10 HB 02	M 10x1	G 1/8"-28
GE HMOK 12 HB 02	M 12x1,5	G 1/8"-28
GE HMOK 12 HB 04	M 12x1,5	G 1/4"-19
GE HMOK 14 HB 04	M 14x1,5	G 1/4"-19
GE HMOK 14 HB 06	M 14x1,5	G 3/8"-19
GE HMOK 16 HB 04	M 16x1,5	G 1/4"-19
GE HMOK 16 HB 06	M 16x1,5	G 3/8"-19
GE HMOK 18 HB 06	M 18x1,5	G 3/8"-19
GE HMOK 18 HB 08	M 18x1,5	G 1/2"-14
GE HMOK 20 HB 08	M 20x1,5	G 1/2"-14
GE HMOK 22 HB 08	M 22x1,5	G 1/2"-14
GE HMOK 22 HB 10	M 22x1,5	G 5/8" -14
GE HMOK 22 HB 12	M 22x1,5	G 3/4"-14
GE HMOK 26 HB 12	M 26x1,5	G 3/4"-14
GE HMOK 27 HB 12	M 27x2	G 3/4"-14
GE HMOK 27 HB 16	M 27x2	G 1" -11
GE HMOK 33 HB 16	M 33x2	G 1" -11
GE HMOK 42 HB 20	M 42x2	G 1 1/4"-11
GE HMOK 48 HB 24	M 48x2	G 1.1/2" -11